

CW 4 PT TYPE CABLE GLAND



Technical Details

Size	: 20 mm to 90 mm S & L	Material	: Brass BS 2874 CZ121 Pb3.
Standard	: BS 6121	Options Threads	: METRIC, NPT, BSP & PG.
IP Rating	: IP66	Finish	: Natural Brass Finish, Nickel Finish.
Application	: For indoor or outdoor use with all types of SWA Cable.	Operating Temp.	: Standard seals -20° C to +80° C.
Function	: CW type glands provide a seal on the outer sheath and an armour specific armour clamp for armoured cable. The armour clamp provides an electrical bond armour cable and the gland.	Accessories	: Matching Accessories available like PVC Shrouds, Lock Nuts & Earth Tag.

CODE NO.	GLAND SIZE	THREAD SIZE 'C'		MINIMUM LENGTH OF THREAD 'D'	CABLE RANGE	
		METRIC	INCH		MAX 'A'	MAX 'B'
AT-C4-20S	CW 20S	M20	3/4"	10	11.50	15.50
AT-C4-20L	CW 20L	M20	3/4"	10	14.00	20.50
AT-C4-25S	CW 25S	M25	1"	10	18.00	24.00
AT-C4-25L	CW 25L	M25	1"	10	20.00	27.20
AT-C4-32S	CW 32S	M32	1 1/4"	10	26.30	33.50
AT-C4-32L	CW 32L	M32	1 1/4"	10	26.30	33.50
AT-C4-40S	CW 40S	M40	1 1/2"	13	31.50	39.50
AT-C4-40L	CW 40L	M40	1 1/2"	13	32.00	40.00
AT-C4-50S	CW 50S	M50	2"	13	38.20	46.30
AT-C4-50L	CW 50L	M50	2"	13	44.00	52.60
AT-C4-63S	CW 63S	M63	2 1/2"	14	50.10	59.00
AT-C4-63L	CW 63L	M63	2 1/2"	14	56.00	65.30
AT-C4-75S	CW 75S	M75	3"	15	62.00	71.60
AT-C4-75L	CW 75L	M75	3"	15	68.00	78.00
AT-C4-90S	CW 90S	M90	3 1/2"	20	80.50	91.00
AT-C4-90L	CW 90L	M90	3 1/2"	20	80.50	91.00

Also available in Kit Packing and as per the specification.

All Dimension are Millimeters