

A1 A2 CABLE GLAND



Technical Details

Size	: 20 mm to 90 mm S & L	Material	: Brass BS 2874 CZ121 Pb3.
Standard	: BS 6121	Options Threads	: METRIC, NPT, BSP & PG.
IP Rating	: IP66 & 68	Finish	: Natural Brass Finish, Nickel Finish.
Application	: Outdoor or Indoor for use with all types of Unarmoured Cable.	Operating Temp.	: Standard seals -20° C to +80° C.
Function	: A2 type glands provide a single pull resistant seal on the outer sheath of unarmoured cable.	Accessories	: Matching Accessories available like PVC Shrouds, Lock Nuts & Earth Tag.

CODE NO.	GLAND SIZE	THREAD SIZE 'B'		MINIMUM LENGTH OF THREAD 'C'	CABLE RANGE 'A'	
		METRIC	INCH		MAX.	MIN.
AT-A1-20S	A1/A2 20S	M20	3/4"	10	11.50	8.00
AT-A1-20L	A1/A2 20L	M20	3/4"	10	13.50	11.00
AT-A1-25S	A1/A2 25S	M25	1"	10	16.50	13.00
AT-A1-25L	A1/A2 25L	M25	1"	10	19.50	16.00
AT-A1-32L	A1/A2 32L	M32	1 1/4"	10	25.50	19.00
AT-A12-40S	A1/A2 40S	M40	1 1/2"	15	29.00	23.00
AT-A12-40L	A1/A2 40L	M40	1 1/2"	15	32.00	25.00
AT-A1-50S	A1/A2 50S	M50	2"	15	37.00	31.50
AT-A1-50L	A1/A2 50L	M50	2"	15	43.00	36.50
AT-A1-63S	A1/A2 63S	M63	2 1/2"	15	50.00	42.50
AT-A1-63L	A1/A2 63L	M63	2 1/2"	15	55.00	49.50
AT-A1-75S	A1/A2 75S	M75	3"	15	61.00	54.50
AT-A1-75L	A1/A2 75L	M75	3"	15	67.00	60.50
AT-A1-90	A1/A2 90	M90	3 1/2"	20	78.00	65.00

Also available in Kit Packing and as per the specification.

All Dimension are Millimeters